



BLUE OX

Qualifying a Flat Tow Vehicle

Have you verified that your vehicle is flat towable with the manufacturer & states so in the owner's manual?

Have you verified any restrictions that must be followed with the manufacturer & states so in your owner's manual?

What rating is the motor home capable of towing? _____

What is the rating of the receiver hitch on the motorhome? _____

There are many components that must be used to flat tow a vehicle behind your motor home, here is what you will need:

Tow Bar

Choose a tow bar that matches vehicle weight & tab width of the baseplate.

Vehicle Weight

Tab Width

Tow Bar Part # _____

Baseplate

Installs on the frame of your vehicle, cutting & modifications are required.

Go to the blueox.com Baseplate Finder

Vehicle _____

Baseplate Part # _____

Supplemental Brake BRK2022

The Patriot brake provides braking to the towed vehicle, reduces wear on the coach brakes & premature wear to the tow bar. Supplemental brakes are required in most states.

We strongly recommend a supplemental brake to be used whenever you flat tow.

12 Volt Power Outlet Kit BX88459

Required when installing Patriot Brake system, power source for braking system

Accessory Kit

Provides essential accessories: tow bar cover, 3 lock set, 7-6 coiled cable & hitch immobilizer.

2" or 2.5" Reciever? _____

Accessory Kit Part # _____

Wiring Kit or Tow Light Kit

Tow Light Kit, EZ Light Kits, Diodes or Bulb and Socket Kit (the blueox.com baseplate page for your specific vehicle will specify the type of wiring kit available).

Wiring Kit Part # _____

Progressive Lit Vehicle Taillight Wiring Kit BX88442

Progressive Lit Vehicle Tail Light Wiring Kit, Coach Powered for Chevy Silverado 2500/3500 & GMC Sierra 2500/3500. 6 Wire This kit works with vehicles that have animated/progressive taillights where battery disconnect is required for flat towing.

Tow Light Kit BX88462

Professional, paint-safe lighting solution for flat towing. It mounts directly into any 2" hitch receiver, providing high-visibility signaling without the need for magnetic lights.

Towed Vehicle Charge Line Kit BX88453

Required on vehicles without battery disconnect and Patriot brake connected to towed vehicle battery

Manual Battery Disconnect BX88443

Battery can be disconnected by simply rotating the switch to the OFF position. Quicker and safer than manually disconnecting the battery each time. Rated at 275-amp constant duty and 1250-amp surge capability. Works on 12-volt batteries. Can be used with diesel and other vehicles with cold cranking amps.

Adjustable Rise/Drop

To prevent premature wear and or damage the tow bar must be +/- 3" from level. The coach receiver hitch must be measured from the ground to center of receiver hitch on a level surface.

2" or 2.5" Receiver? _____

Measurement? _____

Part # _____

KarGard Protective Shield BX8870

Keeps rock chips on the paint of the towed vehicle to a minimum. Installed on the tow bar at the triple lug on both tow bar legs.

