



Qualifying a Flat Tow Vehicle

Have you verified that your vehicle is flat towable with the manufacturer & in the owner's manual?

Have you verified any restrictions that must be followed with the manufacturer & in your owner's manual?

What rating is the motor home capable of towing? _____

What is the rating of the receiver hitch on the motorhome? _____

There are many components that must be used to flat tow a vehicle behind your motor home, here is what you will need:

Tow Bar

Choose a tow bar that matches vehicle weight & tab width of the baseplate.

VEHICLE WEIGHT _____ **TAB WIDTH** _____

Go to the blueox.com Baseplate Finder

Baseplate

Installs on the frame of your vehicle, cutting & modifications are required.

VEHICLE _____
BASEPLATE PART # _____

Wiring Kit

EZ Light Kits, Diodes or Bulb and Socket Kit (the blueox.com baseplate page for your specific vehicle will specify the type of wiring kit available).

WIRING KIT PART # _____

Accessory Kit

Provides essential accessories: tow bar cover, 3 lock set, 7-6 coiled cable & hitch immobilizer.

2" OR 2/5" RECEIVER? _____

ACCESSORY KIT PART # _____

Supplemental Brake

The Patriot brake provides braking to the towed vehicle, reduces wear on the coach brakes & premature wear to the tow bar. Supplemental brakes are required in most states.

We strongly recommend a supplemental brake to be used whenever you flat tow.

Adjustable Rise/Drop

To prevent premature wear and or damage the tow bar must be +/- 3" from level. The coach receiver hitch must be measured from the ground to center of receiver hitch on a level surface.

2" OR 2/5" RECEIVER? _____

MEASUREMENT _____

The baseplate page for your specific vehicle lists the tab height when installed on your vehicle in its stock suspension height.

KarGard Protective Shield

Keeps rock chips on the paint of the towed vehicle to a minimum. Installed on the tow bar at the triple lug on both tow bar legs.