



Weight Distributing Hitches

SwayPro™



Premium Sway Prevention

Features:

- Evenly distributes weight over axles of the tow vehicle and trailer
- **Noise-free sway prevention never stops working, even in rain or snow**
- Caster in the hitch head constantly centers the trailer
- Spring bars augment the suspensions of the tow vehicle & trailer
- Rotating latches with clamp-on brackets for quick and easy setup
- Backup without disconnecting
- Powder-coated steel construction

Specifications:

- **Tongue weights available: 350, 550, 750, 1000, 1500 & 2000** (2.5" Shank)
- Gross Towing Weight 20K maximum
- 2" receiver. 2-1/2" receiver shank available

TrackPro™



Premium Sway Management

Features:

- Evenly distributes weight over axles of the tow vehicle and trailer
- **Manages sway caused by bad roads, wind, and weather**
- Caster in the hitch head constantly centers the trailer
- Spring bars augment the suspensions of the tow vehicle & trailer
- Rigid L-brackets provide additional points of sway controlling friction
- Backup without disconnecting
- Powder-coated steel construction

Specifications:

- **Tongue weights available: 600 (2 inch ball), 800, 1000 & 1300**
- Gross towing weight: 13K maximum
- 2" receiver, 2-1/2" receiver shank available

2-Point™



Best Value Sway Control

Features:

- Evenly distributes weight over axles of the tow vehicle and trailer
- **Steel-on-steel friction minimizes sway**
- Round spring bars flex for a controlled ride
- L-Brackets keep spring bars in place
- Pre-installed 2-5/16" hitch ball, 600lb LTW pre-installed 2" inch ball
- Powder-coated steel construction

Specifications:

- **Tongue weights available: 600 (2 inch ball), 800, and 1200 lbs**
- Gross towing weight: 12K maximum
- 2" receiver

Determining the Correct Hitch for Your Application

Use as a guideline only for initial hitch options. Tongue weight and RV GVWR must be verified to ensure proper hitch set up. Remember, optional equipment, additional cargo in both vehicle and RV, Tow Vehicle GCWR, Tow Vehicle weight rating, and RV GVWR must be accounted for when determining the hitch. You are responsible for your purchase and operation of your hitch.

SwayPro

Blue Ox Part #	Tongue Weight Capacity	Dry Weight Min	Dry Weight Max	GVWR Min	GVWR Max
BXW0350	200-350lb	1050	1850	1300	2300
BXW0550	351-550lb	1851	2900	2301	3700
BXW0750	551-750lb	2901	4000	3701	5000
BXW1000	751-1000lb	4001	5300	5001	6600
BXW1500	1001-1500lb	5301	8000	6601	10000
BXW2000	1501-2000lb, 2.5" Receiver	8001	10500	10001	13400
Underslung Coupler					
BXW0553	351-550lb	1851	2900	2301	3700
BXW0753	551-750lb	2901	4000	3701	5000
BXW1003	751-1000lb	4001	5300	5001	6600
BXW1503	1001-1500lb	5301	8000	6601	10000
BXW2003	1501-2000lb, 2.5" Receiver	8001	10500	10001	13400

TrackPro

Blue Ox Part #	Tongue Weight Capacity	Dry Weight Min	Dry Weight Max	GVWR Min	GVWR Max
BXW0650	350-600lb, 2" ball	1800	3100	2300	4000
BXW0850	601-800lb	3101	4200	4001	5300
BXW1050	801-1000lb	4201	5200	5301	6600
BXW1350	1001-1300lb	5201	6800	6601	8700
Underslung Coupler					
BXW0853	601-800lb	3101	4200	4001	5300
BXW1053	801-1000lb	4201	5200	5301	6600
BXW1353	1001-1300lb	5201	6800	6601	8700

2-Point

Blue Ox Part #	Tongue Weight Capacity	Dry Weight Min	Dry Weight Max	GVWR Min	GVWR Max
BXW0673	350-600lb, 2" ball	1800	3100	2300	4000
BXW0873	601-800lb	3101	4200	4001	5300
BXW1273	801-1200lb	4201	6300	5301	8000

Adjustable Ball Mounts



Pre-installed 2" ball.
Adjustable in height for level towing.
Included clamshell converts 2" ball to 2-5/16".

- BXH10141 4" Drop/Rise 2" Receiver, 10K
- BXH10171 7" Drop/Rise 2" Receiver, 10K
- BXH12241 4" Drop/Rise 2-1/2" Receiver, 12K
- BXH12271 7" Drop/Rise 2-1/2" Receiver, 12K

Clamshell Adapter



BX88377 2" to 2-5/16" Clamshell Adapter

Hitch Locks



- BX88351 Trailer Coupler Lock 1-7/8"-2-5/16"
- BX888360 Universal King Pin Lock
- BX88402 Universal & Adjustable Pin Style Coupler Lock
- BX88403 Pin Style Coupler Lock & 5/8" x 3" Receiver Lock
- BX88212 Receiver Lock 5/8" x 4" for 2-1/2" Receiver
- BX8858 Receiver Lock 5/8" x 2"

Hitch Immobilizers



- BX88371 2" Single Pull Immobilizer
- BX88372 2-1/2" Single Pull Immobilizer
- BX88399 3" Single Pull Immobilizer